

# Zeru



## Designed for Choice. Engineered for Efficiency

Zeru combines **attractive design** with **smart modularity**.

Crafted in full aesthetic alignment with the Neo Q and Neo Q S models, it features a **sleek and refined design** that captures attention even from the most demanding users. A perfect balance of functionality, modularity, and smart design.

Based on an advanced foam-insulated cabinet and efficient R290 components, Zeru guarantees reduced energy consumption and achieves Class C energy efficiency.



### Flexible and configurable

Combine a main unit — hot vending machine or one with an integrated payment module — with up to two satellite modules to increase overall capacity.



### Large capacity

Zeru features a large recollection area for bulky items and can be configured with up to 7 shelves and 80 selections.



### Attractive Design

Elegant, eye-catching design with optimized visibility and lighting. Fully aligned with Neo Q and Neo Q S.



### Theft and vandalism protection

Equipped with an automatic closing mechanism, a dispense sensor, and a reinforced anti-vandalism payment module for maximum security and reliability.

# Zeru

	Zeru Core 6	Zeru Core 8	Zeru Satellite 8	Zeru Satellite10
<b>Max. Capacity</b>				
Channels per shelf	6	8	8	10
Shelves	8	8	8	8
Selections	48	64	64	80
<b>Standard configuration</b>				
Shelves	6	6	6	6
Selections	29	38	38	48
Capacity	278	370	370	445
<b>Configuration</b>				
Protocols	MDB, EXE, EVA-DTS	MDB, EXE, EVA-DTS	-	-
User interface	Keyboard	Keyboard	-	-
Temperature range	+3°C – 18°C	+3°C – 18°C	+3°C – 18°C	+3°C – 18°C
Food safety control	By shelf	By shelf	(depending on Master)	(depending on Master)
Elevator	-	-	○	○
Anti-theft closing mechanism	●	●	●	●
Dispense sensor	●	●	●	●
Lock	Rielda	Rielda	Rielda	Rielda
<b>Payment</b>				
Prepared for coin system	●	●	-	-
Anti-vandalic coin entry	●	●	-	-
Prepared for cashless systems	●	●	-	-
<b>Technical Data</b>				
Dimensions (h x w x d) mm.	1.830 x 705 x 890	1830 x 850 x 890	1830 x 710 x 890	1830 x 850 x 890
Depth with door open	1.530 mm	1.675 mm	1.530 mm	1.675 mm
Voltage / Frequency	230 V / 50 Hz	230 V / 50 Hz	230 V / 50 Hz	230 V / 50 Hz
Max. power consumption	500 W	500 W	500 W	500 W
Weight	235 kg	270 kg	225 kg	265 kg
Cooling technology	R290	R290	R290	R290
Energy efficiency	C	C	C	C

● Standard | ○ Optional